

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

U.S. APPLICATION NO. (If known see 37 C.F.R. 1.5)

09/647951

INTERNATIONAL APPLICATION NO.

PCT/JP00/00658

INTERNATIONAL FILING DATE

07 February 2000

(EARLIEST) PRIORITY DATE CLAIMED

08 February 1999

TITLE OF INVENTION

INFORMATION RECORDING/PLAYBACK SYSTEM

APPLICANTS FOR DO/EO/US

Tomoyuki ASANO and Yoshitomo OSAWA

Applicants herewith submit to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)), including **14** sheets of formal drawings and a copy of the International Search Report.
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventors (35 U.S.C. 371(c)(4)).
10. ☐ The annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:

PCT/ISA/210, PCT/IB/301, 304 and 308

PCT/RO/101

References for IDS

EXPRESS MAILMailing Label Number: EL588273813USDate of Deposit: October 6, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service

"Express Mail Post Office to Addressee" Service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents and Trademarks, Box PCT Washington, DC 20231

Edward Nam
(Typed or printed name of person mailing paper or fee)Edward Nam
(Signature of person mailing paper or fee)

U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.50)

INTERNATIONAL APPLICATION NO.

ATTORNEY'S DOCKET NO.

PCT/JP00/00658

45010102326

09/647961
17. ☒ The following fees are submitted:

(CALCULATIONS /PTO USE ONLY)

Basic National Fee (37 CFR 1.492(a)(1)-(5):

Neither international preliminary examination fee (37 CFR 1.482) nor
international search fee (37 CFR 1.445(a)(2)) paid to USPTO and
International Search Report not prepared by the EPO or JPO... \$1000.00

International preliminary examination fee (37 C.F.R. 1.482)
not paid to USPTO but International Search Report prepared
by the EPO or JPO.....\$ 860.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)
Not paid to USPTO but international search fee (37 CFR 1.445(a)(2))
paid to USPTO (37 CFR 1.445(a)(2)).....\$ 710.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)
But all claims did not satisfy provisions of PCT Article 33(1)-(4).....\$ 690.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)
and all claims satisfied provisions of PCT Article 33(1)-(4).....\$ 100.00

ENTER APPROPRIATE BASIC FEE AMOUNT = (\$ 860.00)

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)). (\$ /

78 Claims /Number Filed / Number Extra /Rate (

Total Claims / 78 - 20 = / 58 /X \$18.00 (\$1,044.00

Independent Claims / 11 - 3 = / 8 /X \$80.00 (\$ 640.00

Multiple dependent claim(s) (if applicable) /+ \$260.00 (\$

TOTAL OF ABOVE CALCULATIONS = (\$ 2,544.00

Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity (statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28). (/

SUBTOTAL = (\$ 2,544.00

Processing fee of \$130.00 for furnishing the English translation later than (/
☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(f)).+ (\$ /

TOTAL NATIONAL FEE = (\$ 2,544.00

Fee for recording the enclosed assignments (37 CFR 1.21(h)). The assignment (\$ 0.00/
must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) \$40.00 per property + (\$ /

TOTAL FEES ENCLOSED = (\$ 2,544.00

(Amount to be: /
(refunded /\$
(charged /\$

- a. ☒ Our check in the amount of **\$2,544.00** to cover the above fees is enclosed.
b. ☐ Please charge my Deposit Account No. **50-0320** in the amount of \$_____ to cover the above fees.
A duplicate copy of this sheet is enclosed.
c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. **50-0320**. A duplicate copy of this sheet is enclosed.
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

WILLIAM S. FROMMER
FROMMER LAWRENCE & HAUG LLP
745 FIFTH AVENUE
NEW YORK, NEW YORK 10151

SIGNATURE

WILLIAM S. FROMMER
NAME

25,506
REGISTRATION NUMBER

Dated: October 6, 2000

4/PRTS

09/647961

528 Rec'd PCT/PTO 06 OCT 2000

1

DESCRIPTION

INFORMATION RECORDING/PLAYBACK SYSTEM

Technical Field

The present invention relates to an information recording/playback system which prevents illegal copying of recording media, and to an information recording apparatus, an information playback apparatus, an authentication data recording apparatus, an authentication processing apparatus, an information recording/playback method, an information recording method, an information playback method, an authentication data recording method, an information-recording-medium authentication method, and an information recording medium.

Background Art

In recent years, apparatuses for transmitting and recording digital data such as music information and video information have come to be widely used in households. Since data can be recorded and read with high quality in these apparatuses, it is possible to construct a recording system in which there is no deterioration in quality even if copying is performed repeatedly. Such a recording system must include a copyright protection function to prevent copyrighted data from being illegally copied.

As such a system for the protection of copyright, for example, there is a content

scrambling system in a digital video disc (DVD) ROM.

In this system, all copyrighted data on a disk is encrypted and only an apparatus which has received a license is given an encryption key for obtaining meaningful data by decrypting encrypted data. The licensed apparatus is designed to conform with operation specifications so that illegal copying may not be performed.

However, the method employed in a DVD system such as that described above is effective for ROM media, but it is not effective for RAM media in which data can be recorded by a user. The reason for this is that, in RAM media, although an unauthorized person cannot decrypt encrypted data, the person can newly create a disk which operates in an authorized apparatus by copying all the data on a disk to a new disk.

Disclosure of the Invention

Accordingly, an object of the present invention is to provide an information recording/playback system constituting an illegal-copying prevention system which is also effective for RAM media, and to provide an information recording apparatus, an information playback apparatus, an authentication data recording apparatus, an authentication processing apparatus, an information recording/playback method, an information recording method, an information playback method, an authentication data recording method, an information-recording-medium authentication method, and an information recording medium.

The present invention is an information recording/playback system for recording and playing back information and is characterized by comprising: an authentication data recording control part which provides control of detecting random pattern information based on random physical phenomena from a random-pattern-information recording part used for recording such random-physical-phenomena-based random pattern information on an information recording medium; generating medium identification information from the random pattern information; and recording the medium identification information as authentication data in the authentication data recording part on the information recording medium; an authentication processing part which detects the random pattern information from the random-pattern-information recording part, generates medium-identification-information verification data from the random pattern information; reads authentication data from the authentication data recording part on the information recording medium; and performs authentication processing for the information recording medium based on medium-identification-information verification data generated from the random pattern information and based on the authentication data; and an information recording/playback control part which provides control of recording information on an information recording medium and playing back information from an information recording medium based on an authentication result from the authentication processing part.

Furthermore, the present invention is an information recording apparatus for

recording information on an information recording medium including: a random-pattern-information recording part which records random pattern information based on random physical phenomena; and an authentication data recording part which stores, as authentication data; medium identification information created according to random pattern information detected from the random-pattern-information recording part, and is characterized by comprising: a random-pattern-information detection part which detects random pattern information from the random-pattern-information recording part on the information recording medium; a verification data creation part which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection part; an authentication processing part which reads authentication data from the authentication data recording part on the information recording medium; performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation part and based on the authentication data; and controls whether to enable writing information onto an information recording medium based on an authentication result; and a recording control part which provides control of recording information onto an information recording medium.

Furthermore, the present invention is an information playback apparatus for playing back information from an information recording medium including: a random-pattern-information recording part which records random pattern information

based on random physical phenomena; and an authentication data recording part which stores; as authentication data; medium identification information created according to random pattern information detected from the random-pattern-information recording part; and is characterized by comprising: a random-pattern-information detection part which detects random pattern information from the random-pattern-information recording part on the information recording medium; a verification data creation part which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection part; an authentication processing part which reads authentication data from the authentication data recording part on the information recording medium, and performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation part and based on the authentication data; and a playback control part which provides control of reading information from an information recording medium.

In an authentication data recording apparatus which records authentication information on an information recording medium, the present invention is characterized by comprising: a random-pattern-information detection part which detects random pattern information from a random-pattern-information recording part on an information recording medium used for recording random pattern information based on random physical phenomena; a medium identification information creation part which creates medium identification information from the random pattern

information detected by the random-pattern-information detection part; and an authentication data recording control part which provides control of recording, as authentication data, medium identification information created by the medium identification information creation part by using an authentication data recording part on the information recording medium.

In an authentication processing apparatus which performs authentication processing for an information recording medium, the present invention is characterized by comprising: a random-pattern-information detection part which detects random pattern information from a random-pattern-information recording part on the information recording medium; a verification data creation part which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection part; and an authentication processing part which plays backs authentication data from a authentication data recording part on an information recording medium and performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation part and based on the authentication data.

Further, the present invention is an information recording/playback method for recording and playing back information, and is characterized by comprising: an authentication data recording control process which detects random pattern information based on random physical phenomena from a random-pattern-information

recording part used for recording random pattern information based on random physical phenomena on an information recording medium, creates medium identification information from the random pattern information, and controls recording; as authentication data; the medium identification information in an authentication data recording part on the information recording medium; an authentication process which detects the random pattern information from the random-pattern-information recording part; creates medium-identification-information verification data from the random pattern information; reads authentication data from an authentication data recording part on the information recording medium; and performs authentication processing for the information recording medium based on medium-identification-information verification data created from the random pattern information and based on the authentication data; and an information recording/playback control process which provides control of recording information on an information recording medium and playing back information from an information recording medium based on an authentication result from the authentication process.

Furthermore, the present invention is an information recording method for recording information on an information recording medium including: a random-pattern-information recording part which records random pattern information based on random physical phenomena; and an authentication data recording part which stores, as authentication data, medium identification information created according to

random pattern information detected from the random-pattern-information recording part; and is characterized by comprising: a random-pattern-information detection process which detects random pattern information from a random-pattern-information recording part on an information recording medium; a verification data creation process which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection process; an authentication process which reads authentication data from the authentication data recording part on an information recording medium; performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation process and based on the authentication data; and controls whether to enable writing information onto an information recording medium based on an authentication result; and a recording control process which provides control of recording information onto an information recording medium.

Furthermore, the present invention is an information playback method for playing back information from an information recording medium including: a random-pattern-information recording part which records random pattern information based on random physical phenomena; and an authentication data recording part which stores; as authentication data, medium identification information created according to random pattern information detected from the random-pattern-information recording part; and is characterized by comprising: a random-pattern-information detection

process which detects random pattern information from a random-pattern-information recording part on an information recording medium; a verification data creation process which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection process; an authentication process which reads authentication data from an authentication data recording part on the information recording medium; and performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation process and based on the authentication data; and a playback control process which controls reading information from an information recording medium.

In an authentication data recording method which records authentication information on an information recording medium, the present invention is characterized by comprising: a random-pattern-information detection process which detects random pattern information from a random-pattern-information recording part on an information recording medium used for recording random pattern information based on random physical phenomena; a medium identification information creation process which creates medium identification information from the random pattern information detected by the random-pattern-information detection part; and an authentication data recording control process which provides control of recording, as authentication data; medium identification information created by the medium identification information creation process by using an authentication data recording

part on the information recording medium.

In an authentication processing method which performs authentication processing for an information recording medium, the present invention is characterized by comprising: a random-pattern-information detection process which detects random pattern information from a random-pattern-information recording part on an information recording medium; a verification data creation process which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection process; and an authentication process which plays back authentication data from an authentication data recording part on an information recording medium, and performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation process and based on the authentication data.

With respect to information recording medium for recording information, the present invention is characterized by comprising: a random-pattern-information recording part which records random pattern information based on random physical phenomena; an authentication data recording part which stores, as authentication data, medium identification information created according to random pattern information detected from the random-pattern-information recording part; and an information recording part for recording information.

Brief Description of the Drawings

FIG. 1 is a view illustrating an optical disk to which the present invention is applied;

FIG. 2 is a block diagram showing the construction of an authentication data recording apparatus for recording authentication data on the optical disk;

FIG. 3 is a flowchart showing specific processing contents of an authentication data creation part in the authentication data recording apparatus;

FIG. 4 is a block diagram showing the construction of an optical disk recording/playback apparatus which uses the optical disk;

FIG. 5 is a flowchart showing specific processing contents of an authentication processing part in the optical disk recording/playback apparatus;

FIG. 6 is a view showing a revocation list used for authentication processing by the authentication processing part;

FIG. 7 is a view showing a public key list used for authentication processing by the authentication processing part;

FIG. 8 is a block diagram showing the construction of an encryption part of a recording/playback circuit of the optical disk recording/playback apparatus;

FIG. 9 is a view schematically showing the structure of data recorded on an optical disk by the optical disk recording/playback apparatus;

FIG. 10 is a block diagram showing the construction of a decryption part of the recording/playback circuit in the optical disk recording/playback apparatus;

FIG. 11 is a flowchart showing the operation of a recording mode of the optical disk recording/playback apparatus;

FIG. 12 is a flowchart showing the operation of a playback mode of the optical disk recording/playback apparatus;

FIG. 13 is a block diagram showing another example of the construction of an encryption part of the recording/playback circuit in the optical disk recording/playback apparatus;

FIG. 14 is a block diagram showing another example of the construction of a decryption part of the recording/playback circuit in the optical disk recording/playback apparatus; and

FIG. 15 is a view illustrating a card-shaped information recording medium to which the present invention is applied.

Best Mode For Carrying Out the Invention

The best mode for carrying out the present invention is described in detail below with reference to the drawings.

The present invention is applied to a recording/playback system employing, for example, an optical disk 1 having a construction such as that shown in FIG. 1.

The optical disk 1 shown in FIG. 1 is a disk medium into which and from which information can be recorded/played back, and has a user data recording part 3, a random-pattern-information recording part 4, and an authentication data recording part

5, which are three information recording areas formed annularly around a center hole 2 at the center. The user data recording part 3, the random-pattern-information recording part 4, and the authentication data recording part 5 are placed, for example, so as to be separated in a two-dimensional manner or separated in a three-dimensional manner so that these parts can be accessed independently of each other in order to read information.

In this optical disk 1, the information recording area is separated in a two-dimensional manner in the radial direction of the disk, thereby forming the user data recording part 3, the random-pattern-information recording part 4, and the authentication data recording part 5.

In this optical disk 1, the user data recording part 3 formed in the periphery thereof is a data area in which user data is recorded or played back. Namely, this area records contents such as video, music, and the like.

Also, the random-pattern-information recording part 4 which is formed in a central part thereof is a read-only area in which random pattern information based on random physical phenomena is recorded.

This random-pattern-information recording part 4 is formed by randomly scattering, for example, fine magnetized fibers in the area of this random-pattern-information recording part 4 and by fixing them when the medium is manufactured. The random-pattern-information recording part 4 formed in this manner is one in which the random pattern information in the fine magnetized fibers

is recorded so that it can be detected.

The random-pattern-information recording part 4 may be such that bits are randomly formed and the jitter thereof can be detected as random pattern information.

Furthermore, the authentication data recording part 5 which is formed in the outer periphery of the random-pattern-information recording part 4 is an area in which medium identification information created based on the random pattern information detected from the random-pattern-information recording part 4 and a digital signature for each manufacturer with respect to the medium identification information are recorded as authentication data. This authentication data recording part 5 is provided in a lead-in area.

In the optical disk 1 having such a construction, authentication data is recorded in the authentication data recording part 5 by an authentication data recording apparatus 10 constructed, for example, as shown in FIG. 2.

This authentication data recording apparatus 10 shown in FIG. 2 comprises a spindle motor 12 controlled by a servo circuit 11, a recording/playback head 13 which optically scans the information recording surface of the optical disk 1, a random-pattern-information detection part 14 for detecting random pattern information from the random-pattern-information recording part 4 of the optical disk 1, a medium-identification-information creation part 15 for creating medium identification information r, an authentication data creation part 16 for creating authentication data, and a control section 18 for controlling the servo circuit 11 and the authentication data

creation section 16 on the basis of the setting information input from an input operation section 17.

The spindle motor 12 drivingly rotates the optical disk 1, for example, at a constant linear velocity under the control of the servo circuit 11.

The recording/playback head 13, which comprises an optical head for optically scanning the authentication data recording part 5 of the optical disk 1 which is drivingly rotated by the spindle motor 12, records and plays back authentication data via the authentication data recording part 5.

The random-pattern-information detection part 14 comprises a magnetic head for scanning the random-pattern-information recording part 4 of the optical disk 1 which is drivingly rotated by the spindle motor 12, and detects in an analog manner the random pattern information from the random-pattern-information recording part 4. This random-pattern-information detection part 14 supplies the random pattern information detected from the random-pattern-information recording part 4 to the medium-identification-information creation part 15.

The medium-identification-information creation part 15 converts the random pattern information detected in an analog manner by the random-pattern-information detection part 14 into digital random pattern information, and supplies this information as medium identification information r to the authentication data creation part 16.

The authentication data creation part 16 affixes a digital signature for each manufacturer with respect to the medium identification information r, to the medium

identification information r supplied from the medium identification information creation part 15 in order to use it as authentication data.

Here, in creating authentication data to which a digital signature for each manufacturer is affixed by the authentication data creation part 16, the manufacturer for the recording medium uses a trusted center (TC), and registers its own public key required for the verification of the digital signature in the TC so as to request the TC to issue a certificate (Cert) in advance. The certificate (Cert) is data in which the TC has made a digital signature on the identification information ID of the manufacturer, the public key, etc.

The digital signature technology is a technology capable of certifying that a person who created particular data is a particular user. For example, an elliptic curve digital signature algorithm (EC-DSA) method used in the IEEE P1363 is well known.

In this authentication data recording apparatus 10, as the specific processing contents of the authentication data creation part 16 are shown in FIG. 3, additional information u such as the manufacturing date of the medium and the manufacturer ID is added to the medium identification information r supplied from the medium identification information creation part 15 in order to create data m (step S1). For this data m , digital signature data s is created by using a secret key for each manufacturer corresponding to the public key registered in the trusted center (step S2).

The additional information u is data which may be added to the medium identification information r as required.

Then, the authentication data creation part 16 combines the data m , the digital signature data s , the certificate (Cert) data, and the revocation list into authentication data w (step S3), and supplies this authentication data w to the recording/playback head 13 (step S4), whereby it is written in the authentication data recording part 5 of the optical disk 1.

Here, the additional information u , the secret key for each manufacturer, and the certificate (Cert) data are input, for example, from the input operation part 17 to the control part 18, whereby it is provided from the control part 18 to the authentication data creation part 16.

In this authentication data recording apparatus 10, the revocation list provided from the trusted center is input from the input operation part 17 to the control part 18, whereby the revocation list is provided from the control part 18 to the authentication data creation part 16 so that the revocation list can be recorded in the authentication data recording part 5 of the optical disk 1. In the authentication data recording part 5 of the optical disk 1, the latest revocation list provided from the trusted center is recorded.

Here, the revocation list is such that the trusted center has made a digital signature on the version number thereof which increases monotonously and the identification information ID of the manufacturer to which the secret key has been revealed and which is determined to have committed a fraud.

The manufacturer of the recording medium is able to manufacture the optical

disk 1 in which the data m , the digital signature data s , the certificate (Cert) data, and the revocation list are recorded as authentication data w in the authentication data recording part 5 by the authentication data recording apparatus 10 constructed as described above.

The optical disk 1 having such a construction is capable of verifying the validity by authentication processing by the random pattern information detected from the random-pattern-information recording part 4 in which random pattern information from a random physical phenomenon is recorded, and the authentication data recorded in the authentication data recording part 16. The random pattern information recorded in the random-pattern-information recording part 4 cannot be reproduced because it is from a random physical phenomenon.

In the optical disk 1 having a construction such as that described above, data is recorded or played back, for example, by an optical disk recording/playback apparatus 20 having a construction such as that shown in FIG. 4.

The optical disk recording/playback apparatus 20 shown in FIG. 4 comprises a spindle motor 22 controlled by a servo circuit 21; a recording/playback head 23 which optically scans the information recording surface of the optical disk 1; a random-pattern-information detection part 24 for detecting random pattern information from the random-pattern-information recording part 4 of the optical disk 1; a medium-identification-information verification-data creation part 25 for creating medium-identification-information verification data r' ; an authentication processing

part 26; a recording/playback part 27; and a control part 19 for controlling the servo circuit 21 and the recording/playback part 27 on the basis of setting information input from an input operation part 28.

The spindle motor 22 drivingly rotates the optical disk 1, for example, at a constant linear velocity under the control of the servo circuit 21.

The recording/playback head 23 comprises an optical head for optically scanning the information recording surface of the authentication data recording part 5 of the optical disk 1 which is drivingly rotated by the spindle motor 22. The recording/playback head 23 plays back the authentication data recorded in the authentication data recording part 5, and records data on and plays back data from the user data recording part 3.

The random-pattern-information detection part 24 comprises a magnetic head for scanning the random-pattern-information recording part 4 of the optical disk 1 which is drivingly rotated by the spindle motor 22, and detects in an analog manner random pattern information from the random-pattern-information recording part 4. This random-pattern-information detection part 24 supplies the random pattern information detected from the random-pattern-information recording part 4 to the medium-identification-information verification-data creation part 25.

The medium-identification-information verification-data creation part 25 accomplishes a conversion from information detected by the random-pattern-information detection part 24 in an analog manner to digital random

pattern information and supplies this information as medium-identification-information verification data r' to the authentication processing part 26.

The authentication processing part 26 performs a process for authenticating that the optical disk 1 is manufactured by an authorized manufacturer. The recording/playback part 27 supplies this authentication processing part 26 with authentication data w^\wedge which is read by the recording/playback head 23 from the authentication data recording part 5 of the optical disk 1. The authentication processing part 26 performs an authentication process on the basis of the medium-identification-information verification data r' supplied from the medium-identification-information creation part 25 and the authentication data w^\wedge .

The specific processing contents of the authentication processing part 26 are shown in FIG. 5.

More specifically, when the medium-identification-information verification data r' and the authentication data w^\wedge are input (step S11), initially, the authentication processing part 26 verifies the validity of the revocation list which is entered in the authentication data w^\wedge , that is, the validity of the digital signature of the trusted center, by using the public key of the trusted center (step S12). The public key of the trusted center is common to the entire system, and is stored in a nonvolatile memory within the apparatus when the apparatus is manufactured.

As a result of the verification of the revocation list, when the revocation list is

valid, the version number of the revocation list is verified (step S13). When the revocation list is compared with the currently stored revocation list and the version number is newer, the revocation list is stored in the nonvolatile memory (step S14). A revocation list such as that shown in FIG. 6 is stored in the nonvolatile memory.

Next, the certificate (Cert) data in the authentication data w^{\wedge} is extracted (step S15). It is verified that the identification information ID of the manufacturer contained in the certificate (Cert) data is not in the revocation list stored in the nonvolatile memory (step S16). Furthermore, it is verified that the digital signature of the trusted center, contained in the certificate (Cert) data, is correct (step S17).

When this verification is passed, data m^{\wedge} and digital signature data s^{\wedge} are extracted from the authentication data w^{\wedge} (step S18). It is verified by using the public key of the manufacturer in the certificate (Cert) data that the digital signature data s^{\wedge} in the authentication data w^{\wedge} is a correct digital signature of the manufacturer with respect to the data m^{\wedge} (step S19).

When this verification is passed, the verification result J2 is assumed to be passed (step S20).

Next, medium identification information r^{\wedge} and additional information u^{\wedge} are extracted from the authentication data w^{\wedge} (step S21).

Then, the medium identification information r^{\wedge} extracted from the authentication data w^{\wedge} is compared with the medium-identification-information verification data r' created by the medium-identification-information creation part 25

in order to verify that the difference is within a predetermined error (step S22). This example uses an allowable error in consideration of a possible error due to noises because digital medium-identification-information verification data r' is generated from random pattern information detected as an analog signal. No allowable error needs to be used when random pattern information is digitally recorded and read.

When this verification is passed, the verification result J1 is assumed to be passed (step S23).

When both the verification result J1 and the verification result J2 are passed, this recording medium is determined to be an authorized one, and the medium identification information r^{\wedge} is supplied as authenticated medium identification information DiscID to the recording/playback part 27 (step S24).

Here, the nonvolatile memory may store a public key list such as that shown in FIG. 7.

In this case, the public key list stores the identification information ID of the manufacturer, the public key thereof, and a flag indicating whether or not the identification information ID is revoked. Furthermore, the public key list stores the version number of the latest version of the revocation lists which have been handled by the apparatus.

When this apparatus obtains a valid revocation list which is newer than any of those handled by the apparatus from the data w^{\wedge} , a revocation flag corresponding to the identification information ID given in that list is set to "YES", that is, is set to be

revoked.

If the identification information ID is not in the table by that time, the item thereof is newly created and the flag is set to “YES”.

In contrast, for those in which the identification information ID is not contained in the latest revocation list, although it is in the table stored by the apparatus, all the flags are set to “NO”, that is, are set not to be revoked. Then, the item of the latest version number is updated.

When the certificate (Cert) data extracted from the authentication data w^{\wedge} is to be verified, the identification information ID of the manufacturer is checked. If the item of the identification information ID is in the stored list, the public key is recorded, and the revocation flag is “NO”, the verification of the certificate (Cert) data is not necessary, and the public key recorded in the table is used.

When the item of the identification information ID is in the list, the flag is “NO”, and the public key is not recorded, the certificate (Cert) data is verified, and when it is correct, the public key is stored in the table.

When the item of the identification information ID is in the list and the flag is “YES”, the result of the verification J2 is assumed to be invalidated.

When the item of the identification information ID is not in the list, the certificate (Cert) data is verified. When it is correct, an item corresponding to the identification information ID is newly created, and the public key is stored. At this time, the flag is set to “NO”.

As a result of having a public key list in this manner, in many cases, a medium manufactured by the same manufacturer is used; in most cases of a second time and thereafter, it is possible to omit the verification of the certificate (Cert) data.

In this optical disk recording/playback apparatus 20, the operations mode of the recording/playback part 27 is switched by the control part 29 in accordance with a control command input from the input operation part 28. This recording/playback part 27 comprises an encryption part 30 and a decryption part 40. In the recording mode, user data input from an external source is encrypted by the encryption part 30, and the encrypted user data is recorded in the user data recording part 3 of the optical disk 1 via the recording/playback head 23. Also, in the playback mode, encrypted user data which is read from the user data recording part 3 of the optical disk 1 by the recording/playback head 23 is decrypted by the decryption part 40, and is output to an external source.

The encryption part 30, as the specific construction thereof is shown in FIG. 8, comprises a Kem generation module 31, a random number generation circuit 32, a Kd encryption/decryption circuit 33, a Ks encryption circuit 34, and a content data encryption circuit 35.

The Kem generation module 31 comprises a Km memory 31A having a master key Km stored therein, and a hash function circuit 31B to which the master key Km is supplied from the Km memory 31A and to which authenticated medium identification information DiscID is supplied from the authentication processing part

26.

The master key K_m is a secret key which is given when the license of copyright is received.

The hash function circuit 31B concatenates an n -bit master key K_m and an m -bit medium identification information $DiscID$ in order to create $(n + m)$ -bit concatenated data ($DiscID \parallel K_m$) in which, for example, the low-order bits are the master key K_m and the high-order bits are the medium identification information $DiscID$, and applies a hash function H to the created concatenated data ($DiscID \parallel K_m$), as shown in the following equation (1):

$$K_{em} = H(DiscID \parallel K_m) \quad (1)$$

in order to create an effective master key K_{em} . Then, the hash function circuit 31B supplies the K_d encryption/decryption circuit 33 with the master key K_m and the effective master key K_{em} created from the authenticated medium identification information $DiscID$.

Here, " \parallel " of $A \parallel B$ means the concatenation of data A and data B . Also, the hash function is a function which outputs data of a fixed length, for example, 64 bits or 128 bits, with respect to input data of an arbitrary length, and is a function such that, when $y (= \text{hash}(x))$ is given, determination of x is difficult and determination of the set of x_1 and x_2 in which $\text{hash}(x_1) = \text{hash}(x_2)$ is also difficult. As representative

one-direction hash functions, MD5 (Message Digest) and SHA (Secure Hash Algorithm) are known. This one-direction hash function is described in detail in “Applied Cryptography (Second Edition), Wiley” written by Bruce Schneier.

Furthermore, the random number generation circuit 32 generates random numbers in which random numbers are used as a sector key K_{si} and a disk key K_d, supplies the sector key K_{si} to the K_s encryption circuit 34 and the content data encryption circuit 35, and supplies the disk key K_d to the K_d encryption/decryption circuit 33 and the K_s encryption circuit 34.

The Kd encryption/decryption circuit 33 encrypts, by the effective master key Kem, the disk key Kd supplied from the random number generation circuit 32 in order to create an encrypted disk key EKd. This encrypted disk key Ekd created by the Kd encryption/decryption circuit 33 is recorded in the lead-in area of the optical disk 1 via the recording/playback head 23. Also, this Kd encryption/ decryption circuit 33 decrypts the encrypted disk key Ekd read from the lead-in area of the optical disk 1 via the recording/playback head 23 in order to create a disk key Kd. This disk key Kd created by the Kd encryption/decryption circuit 33 is supplied to the Ks encryption circuit 35.

Also, the Ks encryption circuit 34 encrypts, by the disk key Kd, the sector key Ksi supplied from the random number generation circuit 32 in order to create an encrypted sector key EKs. This encrypted sector key EKs created by the Ks encryption circuit 34 is recorded in the data area of the optical disk 1 via the

recording/playback head 23.

Furthermore, the content data encryption circuit 35 creates encrypted content data by encrypting, by the sector key K_{si} , the user data supplied as content data from an external source.

This encrypted content data created by the content data encryption circuit 35 is recorded in the data area of the optical disk 1 via the recording/playback head 23.

Here, the data area of the optical disk 1 is formed of a plurality of sectors S_i ($i = 1, 2, \dots$), as shown in FIG. 9. Each sector S_i ($i = 1, 2, \dots$) is formed of the header and the main data part. An encrypted sector key EK_{si} ($i = 1, 2, \dots$) in which the sector key K_{si} is encrypted by the disk key K_d is stored in the header of each sector S_i , and encrypted content data in which the user data is encrypted by the sector key K_{si} is stored in the main data part of each sector S_i . The above $i = 1, 2, \dots$ indicates the sector number. For simplicity, sector numbers are omitted in a part of figures and descriptions.

The decryption part 40, as the specific construction thereof is shown in FIG. 10, comprises a Kem generation module 41, an EK_d decryption circuit 43, an EK_s decryption circuit 44, and a content data decryption circuit 45.

The Kem generation module 41 comprises a K_m memory 41A having stored therein a master key K_m which is a secret key which is given when the license of the copyright is received, and comprises a hash function circuit 41B which generates an effective master key K_{em} by a computation process shown in equation (1) described

above from the master key K_m supplied from the K_m memory 41A and the authenticated medium identification information DiscID provided from the authentication processing part 26. The hash function circuit 41B supplies the EKd decryption circuit 43 with the master key K_m and the effective master key K_{em} created from the authenticated medium identification information DiscID.

This K_{em} generation module 41 is constructed similarly to the K_{em} generation module 31 of the encryption part 30, and may also be used as the K_{em} generation module 31.

The EKd decryption circuit 43 creates the disk key K_d by decrypting, by the effective master key K_{em} , the encrypted disk key Ekd read from the lead-in area of the optical disk 1 by the recording/playback head 23, and supplies the decrypted disk key K_d to the EKs decryption circuit 44.

The EKs decryption circuit 44 creates a sector key K_s by decrypting, by the disk key K_d , the encrypted sector key EKs read from the data area of the optical disk 1 by the recording/playback head 23, and supplies the decrypted sector key K_s to the content data decryption circuit 45.

The content data decryption circuit 45 decrypts, by the sector key K_s , the encrypted content data read from the data area of the optical disk 1 by the recording/playback head 23.

In the optical disk recording/playback apparatus 20 constructed as described above, when a recording mode is set in the control part 29 as a result of a recording

command being input from the input operation part 28, the control part 29 controls the recording/playback part 27 so that the user data is recorded in the optical disk 1 in accordance with the procedure such as that shown in the flowchart of FIG. 11.

In the following description, it is assumed that authentication processing has already been performed on the optical disk 1 by the authentication processing part 26 and user data is recorded on the optical disk 1 which is authenticated to be an authorized one.

In the recording mode, the encryption part 30 of the recording/playback part 27 is in an operating state, and the Kem generation module 31 of the encryption part 30 receives the authenticated medium identification information DiscID from the authentication processing part 26 (step S31), reads the master key Km from the Km memory 31A (step S32), and causes the hash function circuit 31B to create an effective master key Kem from the medium identification information DiscID and the master key Km (step S33).

Next, the Kd encryption/decryption circuit 33 determines whether or not the encrypted disk key Ekd has been recorded in the lead-in area of the optical disk 1 (step S34).

Then, when the encrypted disk key Ekd has not been recorded, the Kd encryption/decryption circuit 33 uses a random number of, for example, 40 bits, generated by the random number generation circuit 32 as a disk key Kd (step S35), creates an encrypted disk key Ekd by encrypting this disk key Kd by the effective

master key K_m , and records this encrypted disk key E_{kd} in the lead-in area of the optical disk 1 (step S36).

When the encrypted disk key E_{kd} has been recorded, the K_d encryption/decryption circuit 33 obtains the disk key K_d by decrypting the encrypted disk key E_{kd} by the effective master key K_m (step S37).

Next, the K_s encryption circuit 34 uses the 40-bit random number generated by the random number generation circuit 32 as a sector key K_{si} (step S38), creates an encrypted sector key $E_{K_{si}}$ by encrypting this sector key K_{si} by the disk key K_d , and records this encrypted sector key $E_{K_{si}}$ in the sector header (step S39).

Then, the content data encryption circuit 35 creates encrypted content data by encrypting the user data by the sector key K_{si} , and records this encrypted content data in the main data part (step S40).

Furthermore, the content data encryption circuit 35 determines whether or not all the user data to be recorded has been recorded (step S41). When there is user data to be recorded, the next sector is accessed (step S42), and the process returns to step S38, whereby processing from step S38 to step S42 is performed repeatedly.

When all the user data has been recorded completely in the data area of the optical disk 1 in this manner, the recording mode is terminated.

Also, in this optical disk recording/playback apparatus 20, when a playback mode is set in the control part 29 as a result of a recording command being input from the input operation part 28, the control part 29 controls the recording/playback part 27

so that the user data is read from the optical disk 1 in accordance with the procedure such as that shown in the flowchart of FIG. 12.

In the following description, it is assumed that authentication processing has already been performed on the optical disk 1 by the authentication processing part 26 and user data is read from the optical disk 1 which is authenticated to be an authorized one.

In the playback mode, the decryption part 40 of the recording/playback part 27 is in an operating state. The Kem generation module 41 of the decryption part 40 receives authenticated medium identification information DiscID from the authentication processing part 26 (step S51), reads the master key Km from the Km memory 41A (step S52), and causes the hash function circuit 41B to create an effective master key Kem from the medium identification information DiscID and the master key Km (step S53).

Next, the EKd decryption circuit 43 creates the disk key Kd by decrypting, by the effective master key Kem, the encrypted disk key Ekd read from the lead-in area of the optical disk 1 (step S54).

Next, the EKs decryption circuit 44 creates a sector key Ksi by decrypting the encrypted sector key EKsi read from the data area of the optical disk 1 (step S55).

Then, the content data decryption circuit 45 decrypts, by the sector key Ks, the encrypted content data read from the data area of the optical disk 1 (step S56).

Furthermore, the content data decryption circuit 45 determines whether all the

content data to be read has been read (step S57). When there is content data to be read, the next sector is accessed (step S58), and the process returns to step S25, whereby processing from step S55 to step S58 described above is performed repeatedly.

When all the required content data has been completely read from the data area of the optical disk 1 in this manner, the playback mode is terminated.

On the optical disk 1 of which user data recording part 3 records user data by means of the optical disk recording/playback apparatus 20, the data area records the encryption key for the user data, that is, the sector key K_s , as the encrypted sector key EK_s encrypted by the disk key K_d . Furthermore, the lead-in area records the disk key K_d as an encrypted disk key EK_d which is encrypted by the effective master key K_{em} created on the basis of the master key K_m and the medium identification information DiscID unique to this optical disk 1. Therefore, playing back the user data is only available on an authorized playback apparatus having the master key K_m and an authentication processing function for performing authentication processing on the medium identification information DiscID based on the medium-identification-information verification data created according to the random pattern information recorded in the random-pattern-information recording part 4 of the optical disk 1 and based on the authentication data recorded in the authentication data recording part 5. Decrypting and playing back the user data is impossible on a playback apparatus which does not have the authentication processing function or the

master key K_m .

Also, even if the data of the data area and the lead-in area of the optical disk 1 is illegally copied as it is into a new disk, since the random pattern information recorded in the random-pattern-information recording part 4 of the optical disk 1 is from a random physical phenomenon, it is not possible to detect, from the random-pattern-information recording part of the new disk, the same random pattern information as the random pattern information recorded in the random-pattern-information recording part 4 of the optical disk 1 even if the new disk is an authorized one including a random-pattern-information recording part. Therefore, an illegally copied disk is not played back by the authorized playback apparatus.

Here, in the optical disk recording/playback apparatus 20, the encryption part 30 creates the effective master key K_{em} from the master key K_m on the basis of the medium identification information DiscID of the optical disk 1 which is authenticated by the authentication processing part 26, encrypts the disk key K_d by this effective master key K_{em} , encrypts an encryption key used for encrypting the user data, that is, the sector key K_s , by the disk key K_d , and records the user data encrypted by the sector key K_s , the encrypted disk key K_d , and the sector key K_s on the optical disk 1. However, the user data may be encrypted based on the medium identification information DiscID of the optical disk 1 which is authenticated by the authentication processing part 26. For example, as shown in FIG. 13, there is provided an effective

sector key creation part 130 (Kes creation circuit) for creating an effective sector Kes from the sector key Ks generated as a random number in the random number generation circuit 32 on the basis of the effective master key Kem. The content data encryption circuit 35 uses the effective sector key Kes created by the sector key creation circuit 130 to encrypt user data and create encrypted content data.

In this case, as shown in FIG. 14, the decryption part 40 is provided with an effective sector key creation circuit (Kes creation circuit) 140 for creating an effective sector key Kes from the sector key Ks on the basis of the effective master key Kem. The EKs decryption circuit 44 uses the disk key Kd to create a sector key Ks by decrypting the encrypted sector key EKs read by the recording/playback head 23 from the data area of the optical disk 1. From this sector key Ks, the effective sector key creation circuit 140 creates an effective sector key Kes. Using this effective sector key Kes, the content data decryption circuit 45 decrypts the encrypted content data.

Although in the above-described embodiment, the present invention is applied to a recording/playback system using the optical disk 1 constructed as shown in FIG. 1, it is also possible to construct a recording/playback system using a card-shaped recording medium 51 such as that shown in FIG. 15.

More specifically, this card-shaped recording medium 51 shown in FIG. 13 comprises a user data recording part 53 in which user data is recorded, a random-pattern-information recording part 54 in which random pattern information from a random physical phenomenon is recorded, and an authentication data recording

part 55 in which medium identification information created on the basis of the random pattern information detected from the random-pattern-information recording part 54, and the digital signature for each manufacturer with respect to the medium identification information are recorded as authentication data.

Like the above-described optical disk recording/playback system, the recording/playback system using the card-shaped recording medium 51 with such a construction detects random pattern information based on random physical phenomena from the random-pattern-information recording part 54, and creates medium identification information from the random pattern information. Furthermore, authentication data is read from the authentication data recording part 55 on the information recording medium, and authentication processing for the information recording medium can be performed based on the medium identification information created from the random pattern information and the authentication data. An encryption key is created from the medium identification information of the information recording medium authenticated by the authentication processing, and data which is encrypted with the encryption key is recorded/read via the user data recording part 53 on the authenticated information recording medium, making it possible to reliably prevent illegal copying of the information of the user data recording part 53.

As has been described above in detail, the embodiment of the present invention detects random pattern information based on random physical phenomena from the

random-pattern-information recording part on the information recording medium which is provided with a random-pattern-information recording part including recorded therein random pattern information based on random physical phenomena, creates medium identification information from the random pattern information, and records, as authentication data, the medium identification information, together with a digital signature for each manufacturer with respect to the medium identification information, in the authentication data recording part on the information recording medium, making it possible to provide an information recording medium which records, as authentication data, medium identification information, together with a digital signature for each manufacturer with respect to the medium identification information, in the authentication data recording part. Then, with respect to the information recording medium including a random-pattern-information recording part including recorded therein random pattern information from a random physical phenomenon, an authentication data recording part including stored therein medium identification information created based on the random pattern information detected from the random-pattern-information recording part, and a digital signature for each manufacturer with respect to the medium identification information as authentication data, and a user data recording part in which user data is recorded, random pattern information based on random physical phenomena is detected from the random-pattern-information recording part, medium identification information is created from the random pattern information, and authentication data is read from the

authentication data recording part on the information recording medium, and authentication processing for the information recording medium can be performed based on the medium identification information created from the random pattern information and the authentication data. An encryption key is created from the medium identification information on the information recording medium authenticated by the authentication processing, and data which is encrypted with the encryption key is recorded/read via the user data recording part on the authenticated information recording medium, making it possible to construct an illegal-copying prevention system which is also effective for writable media.

CLAIMS

1. An information recording/playback system for recording and playing back information, comprising:

an authentication data recording control part which provides control of detecting random pattern information based on random physical phenomena from a random-pattern-information recording part used for recording random pattern information based on random physical phenomena, creating medium identification information from the random pattern information, and recording, as authentication data, the medium identification information in an authentication data recording part on the information recording medium;

an authentication processing part which detects the random pattern information from the random-pattern-information recording part, creates medium-identification-information verification data from the random pattern information, reads authentication data from the authentication data recording part on the information recording medium, and performs authentication processing for the information recording medium based on medium-identification-information verification data created from the random pattern information and based on the authentication data; and

an information recording/playback control part which provides control of recording information on an information recording medium and playing back information from an information recording medium based on an authentication result

encryption part creates an encryption key used for the information encryption by using medium identification information on an information recording medium authenticated by the authentication processing.

6. The information recording/playback system according to claim 1, wherein there is further provided a decryption part for decrypting information by using medium identification information on an information recording medium authenticated by the authentication processing,

wherein the information recording/playback control part provides control of reading encrypted information from the authenticated information recording medium, and

wherein the decryption part decrypts encrypted information read by the information recording/playback control part from an information recording medium by using medium identification information on an information recording medium authenticated by the authentication processing.

7. The information recording/playback system according to claim 6, characterized in that the information recording/playback control part provides control of reading encrypted information and the encryption key used for information encryption from the authenticated information recording medium.

8. The information recording/playback system according to claim 7, wherein the information recording/playback control part provides control of reading encrypted information and the encrypted encryption key from the information recording medium,

and

wherein the decryption part decrypts a read and encrypted encryption key by using medium identification information on an information recording medium authenticated by the authentication processing and decrypts encrypted information by using the encryption key which was encrypted and information thereof is decrypted.

9. The information recording/playback system according to claim 1, wherein the authentication data recording control part records, as authentication data, the medium identification information together with a digital signature of a recording person who recorded the medium identification information in the authentication data recording part on the information recording medium.

10. An information recording/playback system according to claim 9, wherein the authentication data recording control part records a digital signature for a manufacturer of the information recording medium as a digital signature for a recording person who recorded the medium identification information.

11. An information recording apparatus for recording information on an information recording medium including a random-pattern-information recording part for recording random pattern information based on random physical phenomena and an authentication data recording part for storing, as authentication data, medium identification information generated according to random pattern information detected from the random-pattern-information recording part, wherein the information recording apparatus is , comprising:

a random-pattern-information detection part which detects random pattern information from a random-pattern-information recording part on an information recording medium;

a verification data creation part which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection part;

an authentication processing part which reads authentication data from an authentication data recording part on an information recording medium, performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation part and based on the authentication data, and controls whether to write information onto an information recording medium based on an authentication result; and

a recording control part which provides control of recording information on an information recording medium.

12. The information recording apparatus according to claim 11, wherein there is further provided an encryption part which encrypts information by using medium identification information on an information recording medium authenticated by the authentication processing, and

wherein the recording control part provides control of recording information encrypted by the encryption part on the authenticated information recording medium.

13. The information recording apparatus according to claim 12, wherein the recording control part provides control of recording encrypted information and the encryption key used for information encryption on the authenticated information recording medium.

14. The information recording apparatus according to claim 13, wherein the encryption part encrypts information by using the encryption key and encrypts the encryption key used for information encryption by using medium identification information on an information recording medium authenticated by the authentication processing, and

wherein the recording control part provides control of recording information encrypted with the encryption key and the encrypted encryption key on the authenticated information recording medium.

15. The information recording apparatus according to claim 12, characterized in that the encryption part creates an encryption key used for the information encryption by using medium identification information on an information recording medium authenticated by the authentication processing.

16. The information recording apparatus according to claim 11, wherein that the authentication processing part verifies validity of the medium identification information with respect to an information recording medium which records, as authentication data, the medium identification information together with a digital signature of a recording person who recorded the medium identification information

based on the recording person's digital signature, and performs authentication processing with respect to an information recording medium based on medium-identification-information verification data created by the verification data creation part and based on verified valid medium identification information.

17. The information recording apparatus according to claim 16, wherein the authentication processing part verifies validity of the medium identification information with respect to an information recording medium which records a digital signature of a manufacturer for the information recording medium as a digital signature for a recording person of the medium identification information based on the manufacturer's digital signature.

18. The information recording apparatus according to claim 16, wherein the authentication processing part performs authentication processing with respect to an information recording medium which records a revocation list about a recording person together with the authentication data based on the revocation list.

19. The information recording apparatus according to claim 18, wherein the authentication processing part has a storage part for storing the revocation list, stores a revocation list recorded on an information recording medium in the storage part when this revocation list is valid and is newer than the revocation list stored in the storage part, and performs authentication processing based on the revocation list stored in the storage part.

20. An information playback apparatus for playing back information from an

information recording medium including a random-pattern-information recording part for recording random pattern information based on random physical phenomena and an authentication data recording part for storing, as authentication data, medium identification information created according to random pattern information detected from the random-pattern-information recording part, wherein the information playback apparatus,

a random-pattern-information detection part which detects random pattern information from the random-pattern-information recording part on the information recording medium;

a verification data creation part which creates medium-identification-information verification data from random-pattern-information detected by the random-pattern-information detection part;

an authentication processing part which reads authentication data from the authentication data recording part and performs authentication processing with respect to an information recording medium based on medium-identification-information verification data created by the verification data creation part and based on the authentication data; and

a playback control part which provides control of reading information from an information recording medium.

21. The information playback apparatus according to claim 20, wherein the playback control part provides control of reading encrypted information from the authenticated

information recording medium, and

wherein the decryption part decrypts encrypted information read from the information recording medium by the playback control part by using medium identification information on the information recording medium authenticated by the authentication processing.

22. The information playback apparatus according to claim 21, wherein the playback control part provides control of reading encrypted information and an encryption key used for the information encryption from the authenticated information recording medium.

23. The information playback apparatus according to claim 22, wherein the playback control part provides control of reading encrypted information and the encrypted encryption key from the authenticated information recording medium, and

wherein the decryption part decrypts a read and encrypted encryption key by using medium identification information on an information recording medium authenticated by the authentication processing and decrypts encrypted information by using the encryption key which was encrypted and information thereof is decrypted.

24. The information playback apparatus according to claim 20, wherein the authentication processing part verifies validity of the medium identification information with respect to an information recording medium which records, as authentication data, the medium identification information together with a digital signature of a recording person who recorded the medium identification information

based on the recording person's digital signature, and performs authentication processing with respect to the information recording medium based on medium-identification-information verification data created by the verification data creation part and based on verified valid medium identification information.

25. The information playback apparatus according to claim 24, wherein the authentication processing part verifies validity of the medium identification information with respect to an information recording medium which records a digital signature of a manufacturer for the information recording medium as a digital signature for a recording person of the medium identification information based on the manufacturer's digital signature.

26. The information playback apparatus according to claim 24, wherein the authentication processing part performs authentication processing with respect to an information recording medium which records a revocation list about a recording person together with the authentication data based on the revocation list.

27. The information playback apparatus according to claim 26, wherein the authentication processing part has a storage part for storing the revocation list, stores a revocation list recorded on an information recording medium in the storage part when this revocation list is valid and is newer than the revocation list stored in the storage part, and performs authentication processing based on the revocation list stored in the storage part.

28. An authentication data recording apparatus for recording authentication

information on an information recording medium, comprising:

a random-pattern-information detection part which detects random pattern information from a random-pattern-information recording part on an information recording medium for storing random pattern information based on random physical phenomena;

a medium identification information creation part which creates medium identification information from the random pattern information detected by the random-pattern-information detection part; and

an authentication data recording control part which provides control of recording, as authentication data, the medium identification information created by the medium identification information creation part in an authentication data recording part on the information recording medium.

29. The authentication data recording apparatus according to claim 28, wherein the authentication data recording control part records, as authentication data, the medium identification information together with a digital signature for a recording person of the medium identification information in an authentication data recording part on the information recording medium.

30. The authentication data recording apparatus according to claim 28, characterized in that the authentication data recording control part records a digital signature for a manufacturer of the information recording medium as a digital signature for a recording person of the medium identification information.

31. The authentication data recording apparatus according to claim 28, wherein the authentication data recording control part records a revocation list about a manufacturer together with the authentication data in an authentication data recording part on the information recording medium.

32. An authentication processing apparatus for performing authentication processing with respect to an information recording medium, comprising:

a random-pattern-information detection part which detects random pattern information from a random-pattern-information recording part on the information recording medium;

a verification data creation part which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection part; and

an authentication processing part which reads authentication data from an authentication data recording part on the information recording medium and performs authentication processing with respect to the information recording medium based on medium-identification-information verification data created by the verification data creation part and based on the authentication data.

33. The authentication processing apparatus according to claim 32, wherein the authentication processing part verifies validity of the medium identification information with respect to an information recording medium which records, as authentication data, the medium identification information together with a digital

signature of a recording person who recorded the medium identification information based on the recording person's digital signature, and performs authentication processing with respect to the information recording medium based on medium-identification-information verification data created by the verification data creation part and based on verified valid medium identification information.

34. The authentication processing apparatus according to claim 33, wherein the authentication processing part verifies validity of the medium identification information with respect to an information recording medium which records a digital signature of a manufacturer for the information recording medium as a digital signature for a recording person of the medium identification information based on the manufacturer's digital signature.

35. The authentication processing apparatus according to claim 33, wherein the authentication processing part performs authentication processing with respect to an information recording medium which records a revocation list about a recording person together with the authentication data based on the revocation list.

36. The authentication processing apparatus according to claim 35, wherein the authentication processing part has a storage part for storing the revocation list, stores a revocation list recorded on an information recording medium in the storage part when this revocation list is valid and is newer than the revocation list stored in the storage part, and performs authentication processing based on the revocation list stored in the storage part.

37. The authentication processing apparatus according to claim 35, wherein the authentication processing part has a storage part, stores a recording person's identification information and a public key thereof for a manipulated information recording medium together with a revocation flag, updates the revocation flag using a new revocation list, and performs authentication processing based on the revocation list stored in the storage part.

38. An information recording/playback method for recording and playing back information, comprising:

an authentication data recording control process which provides control of detecting random pattern information based on random physical phenomena from a random-pattern-information recording part for recording random pattern information based on random physical phenomena on an information recording medium, creating medium identification information from the random pattern information, and recording, as authentication data, the medium identification information in an authentication data recording part on the information recording medium;

an authentication process which detects the random pattern information from the random-pattern-information recording part, creates medium-identification-information verification data from the random pattern information, reads authentication data from the authentication data recording part on the information recording medium, and performs authentication processing with respect to the information recording medium based on

medium-identification-information verification data created from the random pattern information and based on the authentication data; and

an information recording/playback control process which provides control of recording information on an information recording medium and playing back information from an information recording medium based on an authentication result from the authentication processing process.

39. The information recording/playback method according to claim 38, wherein there is further provided an encryption process which encrypts information using medium identification information from an information recording medium authenticated by the authentication processing, and

wherein the information recording/playback control process provides control of recording information encrypted by the encryption process on the authenticated information recording medium.

40. The information recording/playback method according to claim 39, wherein the information recording/playback control process provides control of recording encrypted information and the encryption key used for information encryption on the authenticated information recording medium.

41. The information recording/playback method according to claim 40, wherein the encryption process encrypts information using the encryption key and encrypts the encryption key used for information encryption using medium identification information on an information recording medium authenticated by the authentication

processing, and

wherein the information recording/playback control process provides control of recording information encrypted with the encryption key and the encrypted encryption key on the authenticated information recording medium.

42. The information recording/playback method according to claim 39, wherein the encryption process creates the encryption key used for information encryption by using medium identification information on an information recording medium authenticated by the authentication processing.

43. The information recording/playback method according to claim 38, wherein the information recording/playback control process provides control of reading encrypted information from the authenticated information recording medium, and

wherein the decryption process decrypts encrypted information read by the information recording/playback control process from an information recording medium by using medium identification information on an information recording medium authenticated by the authentication processing.

44. The information recording/playback method according to claim 43, wherein the information recording/playback control process provides control of reading encrypted information and the encryption key used for information encryption from the authenticated information recording medium.

45. The information recording/playback method according to claim 44, wherein the information recording/playback control process provides control of reading encrypted

information and the encrypted encryption key from the authenticated information recording medium, and

wherein the decryption process decrypts a read and encrypted encryption key by using medium identification information on an information recording medium authenticated by the authentication processing and decrypts encrypted information by using the encryption key which was encrypted and information thereof is decrypted.

46. The information recording/playback method according to claim 38, wherein the authentication data recording control process records, as authentication data, the medium identification information together with a digital signature for a recording person of the medium identification information in an authentication data recording part on the information recording medium.

47. The information recording/playback method according to claim 46, wherein the authentication data recording control process records a digital signature for a manufacturer of the information recording medium as a digital signature for a recording person of the medium identification information.

48. An information recording method for recording information on an information recording medium including: a random-pattern-information recording part which records random pattern information based on random physical phenomena; and an authentication data recording part which stores, as authentication data, medium identification information created according to random pattern information detected from the random-pattern-information recording part, wherein the information

recording method, comprising:

a random-pattern-information detection process which detects random pattern information from a random-pattern-information recording part on an information recording medium;

a verification data creation process which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection process;

an authentication process which reads authentication data from the authentication data recording part on an information recording medium, performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation process and based on the authentication data, and controls whether to enable writing information onto an information recording medium based on an authentication result; and

a recording control process which provides control of recording information onto an information recording medium.

49. The information recording method according to claim 48, wherein there is further provided an encryption process which encrypts information using medium identification information from an information recording medium authenticated by the authentication processing, and

wherein the recording control process provides control of recording information

authenticated by the encryption process on the authenticated information recording medium.

50. The information recording method according to claim 49, characterized in that the recording control process provides control of recording encrypted information and the encryption key used for information encryption on an authenticated information recording medium.

51. The information recording method according to claim 50, wherein the encryption process encrypts information using the encryption key and encrypts the encryption key used for information encryption using medium identification information on an information recording medium authenticated by the authentication processing, and

wherein the recording control process provides control of recording information encrypted with the encryption key and the encrypted encryption key on the authenticated information recording medium.

52. The information recording method according to claim 49, wherein the encryption process creates an encryption key used for the information encryption by using medium identification information on an information recording medium authenticated by the authentication processing.

53. An information recording method according to claim 48, characterized in that the authentication process verifies validity of the medium identification information with respect to an information recording medium which records, as authentication data, the medium identification information together with a digital signature of a recording

information recording medium including a random-pattern-information recording part for recording random pattern information based on random physical phenomena and an authentication data recording part for storing, as authentication data, medium identification information created according to random pattern information detected from the random-pattern-information recording part, wherein the information playback method, comprising:

a random-pattern-information detection process which detects random pattern information from a random-pattern-information recording part on an information recording medium;

a verification data creation process which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection process;

an authentication process which reads authentication data from the authentication data recording part on an information recording medium and performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation process and based on the authentication data; and

a playback control process which provides control of reading information from an information recording medium.

58. The information playback method according to claim 57, wherein the playback control process provides control of reading encrypted information from the

authenticated information recording medium, and

wherein the decryption process decrypts encrypted information read by the playback control process from an information recording medium by using medium identification information on an information recording medium authenticated by the authentication processing.

59. The information playback method according to claim 58, wherein the playback control process provides control of reading encrypted information and the encryption key used for information encryption from the authenticated information recording medium.

60. The information playback method according to claim 59, wherein the playback control process provides control of reading encrypted information and the encrypted encryption key from the information recording medium, and

wherein the decryption process decrypts a read and encrypted encryption key by using medium identification information on an information recording medium authenticated by the authentication processing and decrypts encrypted information by using the encryption key which was encrypted and information thereof is decrypted.

61. The information playback method according to claim 57, wherein the authentication process verifies validity of the medium identification information with respect to an information recording medium which records, as authentication data, the medium identification information together with a digital signature of a recording person who recorded the medium identification information based on the recording

person's digital signature, and performs authentication processing with respect to an information recording medium based on medium-identification-information verification data created by the verification data creation process and based on verified valid medium identification information.

62. The information playback method according to claim 61, wherein the authentication process verifies validity of the medium identification information with respect to an information recording medium which records a digital signature of a manufacturer for the information recording medium as a digital signature for a recording person of the medium identification information based on the manufacturer's digital signature.

63. The information playback method according to claim 61, wherein the authentication process performs authentication processing with respect to an information recording medium which records a revocation list about a recording person together with the authentication data based on the revocation list.

64. The information playback method according to claim 63, wherein the authentication process stores a revocation list recorded on an information recording medium in the storage part when this revocation list is valid and is newer than the already stored revocation list, and performs authentication processing based on the newly stored revocation list.

65. An authentication data recording method for recording authentication information on an information recording medium, comprising:

authentication data recording control process records a revocation list about a manufacturer together with the authentication data in an authentication data recording part on the information recording medium.

69. An authentication processing method for performing authentication processing with respect to an information recording medium, comprising:

a random-pattern-information detection process which detects random pattern information from a random-pattern-information recording part on an information recording medium;

a verification data creation process which creates medium-identification-information verification data from random pattern information detected by the random-pattern-information detection process; and

an authentication process which reads authentication data from the authentication data recording part on an information recording medium and performs authentication processing for an information recording medium based on medium-identification-information verification data created by the verification data creation process and based on the authentication data.

70. The authentication processing method according to claim 69, wherein the authentication process verifies validity of the medium identification information with respect to an information recording medium which records, as authentication data, the medium identification information together with a digital signature of a recording person who recorded the medium identification information based on the recording

person's digital signature, and performs authentication processing with respect to an information recording medium based on medium-identification-information verification data created by the verification data creation process and based on verified valid medium identification information.

71. The authentication processing method according to claim 70, wherein the authentication process verifies validity of the medium identification information with respect to an information recording medium which records a digital signature of a manufacturer for the information recording medium as a digital signature for a recording person of the medium identification information based on the manufacturer's digital signature.

72. The authentication processing method according to claim 70, wherein the authentication process performs authentication processing with respect to an information recording medium which records a revocation list about a recording person together with the authentication data based on the revocation list.

73. The authentication processing method according to claim 72, wherein the authentication process stores a revocation list recorded on an information recording medium in the storage part when this revocation list is valid and is newer than the already stored revocation list, and performs authentication processing based on the newly stored revocation list.

74. The authentication processing method according to claim 72, wherein the authentication process stores a recording person's identification information and a

public key thereof for a manipulated information recording medium together with a revocation flag, updates the revocation flag using a new revocation list, and performs authentication processing based on the revocation list stored in the storage process.

75. An information recording medium for recording information, comprising:

a random-pattern-information recording part which records random pattern information based on random physical phenomena;

an authentication data recording part which stores, as authentication data, medium identification information created according to random pattern information detected from the random-pattern-information recording part; and

an information recording part which records information.

76. The information recording medium according to claim 75, wherein the authentication data recording part records the medium identification information as authentication data together with a digital signature for a recording person of the medium identification information.

77. The information recording medium according to claim 76, wherein the authentication data recording part records a digital signature for a manufacturer of the information recording medium as a digital signature for a recording person of the medium identification information.

78. The information recording medium according to claim 77, wherein the authentication data recording part records a revocation list about a manufacturer together with the authentication data.

ABSTRACT

An information recording medium 1 is provided with: a user data recording part 3 which records user data; a random-pattern-information recording part 4 which records random pattern information from a random physical phenomenon; and an authentication data recording part 5 which records, as authentication data, medium identification information created on the basis of the random pattern information detected from the random-pattern-information recording part 4 and a digital signature for each manufacturer with respect to the medium identification information.




FIG.1




FIG. 2

3/14




FIG.3




FIG.4




FIG.5

6/14

REVOCATION LIST

VERSION NUMBER
MANUFACTURER ID
. . .

FIG.6**PUBLIC KEY LIST**

VERSION NUMBER OF LATEST REVOCATION LIST		
MANUFACTURER ID	PUBLIC KEY	REVOCATION FLAG (YES/NO)
.

FIG.7

7/14




FIG.8




FIG. 9



10/14




FIG.11

11/14




FIG.12




FIG.13





FIG.14



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

Declaration and Power of Attorney for Patent Application**特許出願宣言書及び委任状****Japanese Language Declaration****日本語宣言書**

私は、以下に記名された発明者として、ここに下記の通り宣言する：

As a below names inventor, I hereby declare that:

私の住所、郵便の宛先そして国籍は、私の氏名の後に記載された通りである。

My residence, post office address and citizenship are as stated next to my name:

下記の名称の発明について、特許請求範囲に記載され、且つ特許が認められている発明主題に関して、私は、最初、最先且つ唯一の発明者である（唯一の氏名が記載されている場合）か、或いは最初、最先且つ共同発明者である（複数の氏名が記載されている場合）と信じている。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled.

INFORMATION RECORDING/PLAYBACK SYSTEM

the specification of which is attached hereto unless the following box is checked:

X was filed on February 7, 2000
as United States Application Number of _____
PCT International Application Number PCT/JP00/00658
_____ and was amended on _____
_____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

上記発明の明細書はここに添付されているが、下記の欄がチェックされている場合は、この限りでない：

- ☐ _____ の日に出版され、
この出版の米国出版番号またはPCT国際出版番号は、
_____ であり、且つ
_____ の日に補正された出版（該当する場合）

私は、上記の補正書によって補正された、特許請求範囲を含む上記明細書を検討し、且つ内容を理解していることをここに表明する。

私は、連邦規則法典第37編規則1.56に定義されている、特許性について重要な情報を開示する義務があることを認める。

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the need of the individual case. Any comments on the amount of time you are required to complete this form should be sent to Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS SEND TO: Commissioner of Patents and Trademarks, Washington, DC 20231

Japanese Language Declaration

日本語宣言書

私は、ここに、以下に記載した外国での特許出願または発明者証の出願、或いは米国以外の少なくとも一国を指定している米国法典第35編第365条(a)によるPCT国際出願について、同第119条(a)(d)項又は第365条(b)項に基づいて優先権を主張するとともに、優先権を主張する本出願の出願日より前の出願日を有する外国での特許出願または発明者証の出願、或いはPCT国際出願については、いかなる出願も、下記の枠内をチェックすることにより示した。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT international application having a filing date before that of the application for which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

外国での先行出願

優先権主張なし

11-030600
(Number)
(番号)

Japan
(Country)
(国名)

08 February 1999
(Day/Month/Year Filed)

☐

PCT/JP00/00658
(Number)
(番号)

PCT
(Country)
(国名)

07 February 2000
(Day/Month/Year Filed)

☐

(Number)
(番号)

(Country)
(国名)

(Day/Month/Year Filed)

☐

(Number)
(番号)

(Country)
(国名)

(Day/Month/Year Filed)

☐

(Number)
(番号)

(Country)
(国名)

(Day/Month/Year Filed)

☐

(Number)
(番号)

(Country)
(国名)

(Day/Month/Year Filed)

☐

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、ここに、下記のいかなる米国出願についても、その米国法典第35編第120条に基づく利益を主張し、又米国を指定するいかなるPCT国際出願についても、その同第365条(c)に基づく利益を主張する。また、本出願の各特許請求の範囲の主題が、米国法典第35編第112条第1段に規定された態様で、先行する米国出願又はPCT国際出願に開示されていない場合においては、その先行出願の出願日と本国内出願日またはPCT国際出願日との間の期間中に入手された情報で、連邦規則法典第37編規則1.56に定義された特許性に関わる重要な情報について開示義務があることを承認する。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、ここに表明された私自身の知識に係わる陳述が真実であり、且つ情報と信ずることに基づく陳述が、真実であると信じられることを宣言し、さらに、故意に虚偽の陳述などを行った場合は、米国法典第18編第1001条に基づき、罰金または拘禁、若しくはその両方により処罰され、またそのような故意による虚偽の陳述は、本出願またはそれに対して発行されるいかなる特許も、その有効性に問題が生ずることを理解した上で陳述が行われたことを、ここに宣言する。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

(Status: Patented, Pending, Abandoned)
(現況: 特許許可、係属中、放棄)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

日本語宣言書

委任状： 私は本出願を審査する手続を行い、且つ米国特許商標庁との全ての業務を遂行するために、記名された発明者として、下記の弁理士及び/または弁理士を任命する。(氏名及び登録番号を記載すること)

書類送付先

直通電話連絡先：(氏名及び電話番号)

唯一または第一発明者氏名

発明者の署名

日付

住所

国籍

郵便の宛先

第二共同発明者がいる場合、その氏名

第二共同発明者の署名

日付

住所

国籍

郵便の宛先

(第三以下の共同発明者についても同様に記載し、署名をすること)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

3 WILLIAM S. FROMMER, Registration No. 25,506 and
DENNIS M. SMID, Registration No. 34,930

Send Correspondence to:

WILLIAM S. FROMMER, Esq.

c/o FROMMER LAWRENCE & HAUG LLP

745 Fifth Avenue

New York, New York 10151

Direct Telephone Calls to:

(212) 588-0800

to the attention of:

WILLIAM S. FROMMER

Full name of sole or first inventor

1-04 Tomoyuki ASANO

Inventor's signature

Date

Tomoyuki Asano

02 October 2000

Residence

Kanagawa, Japan

Citizenship

JPF

Japan

Post Office Address

c/o Sony Corporation, 7-35, Kitashinagawa 6-chome,
Shinagawa-ku, Tokyo 141-0001 Japan

full name of second joint inventor, if any

2-04 Yoshitomo OSAWA

Second Inventor's signature

Date

Yoshitomo Osaawa

03 Oct. 2000

Residence

Kanagawa, Japan

Citizenship

JPF

Japan

Post Office Address

c/o Sony Corporation, 7-35, Kitashinagawa 6-chome,
Shinagawa-ku, Tokyo 141-0001 Japan

(Supply similar information and signature for third and subsequent joint inventors)